

## Quick Couplers for Excavators

| Approved for: | Model      | Pin Diameter<br>mm | Pin Centers (x-y)<br>in (mm) | Weight<br>in (kg) |
|---------------|------------|--------------------|------------------------------|-------------------|
| DX55W         | QC45H1G2   | 45                 | 8.6 - 10.5 (218-267)         | 143 (65)          |
| DX60R         | QC45H1G2   | 45                 | 8.6 - 10.5 (218-267)         | 143 (65)          |
| DX80R         | QC45H2G2   | 45                 | 10.3 - 12.2 (262-311)        | 143 (65)          |
| DX140         | QC65H1G2   | 65                 | 13.9 - 16.9 (355-430)        | 404 (183)         |
| DX140LCR      | QC65H1G2   | 65                 | 13.9 - 16.9 (355-430)        | 404 (183)         |
| DX140W        | QC65H1G2   | 65                 | 13.9 - 16.9 (355-430)        | 404 (183)         |
| DX180LC       | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX190W        | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX210W        | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX225LC       | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX235LCR      | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX255LC       | QC80H1G2   | 80                 | 15.2 - 19.7 (385-500)        | 721 (327)         |
| DX300LC       | QH90H-AL-B | 90                 | 18.7 - 22.2 (475-565)        | 961 (436)         |
| DX350LC       | QH100H0-B  | 100                | 20.9 - 24.8 (530-630)        | 1590 (721)        |
| DX420LC       | QH110H0-B  | 110                | 21.1 - 24.2 (535-615)        | 1640 (744)        |
| DX480LC       | QH120H0-B  | 120                | 22.4 - 25.0 (570-635)        | 2403 (1150)       |
| DX520LC       | QH120H0-B  | 120                | 22.4 - 25.0 (570-635)        | 2403 (1150)       |